

PRODUCT SPECIFICATIONS

The high-end LS model brings a sense of elegant luxury, Its beautiful wave-like lines present an elegance that harmonizes with the space, while metallic accents add a glamour that still blends in, and its full-skirted shape creates a sense of luxury.



FEATURES

- The toilet seat has an ergonomic rounded design to ensure comfortable seating。
- CEFIONTECT® ceramic glaze minimizes waste from sticking to porous ceramic surfaces。
- EWATER+® auto-cleans wand, bowl, and under-seat。
- PREMIST® on bowl before each use。
- Ultra high-efficiency dual flush function - 3.8L/3.0L。
- Gentle Aerated, Warm Water, Dual Action Spray with oscillating and pulsating feature。
- Auto lid open/close。
- Auto flush。
- Automatic air deodorizer。
- Heated Seat with Temperature Control。
- Warm Air Dryer function。
- Adjustable spray position。
- Programmable energy saver system。
- Multifunctional horizontal remote control。
- Energy save timer。
- Smooth seam seat design eliminates the gap under the seat。



reddot winner 2022

COMPONENTS

CES8E120KCN

- TCF8E120KCN#W Functional unit
- CS911 T1#XW Toilet unit
- HP101T3#00 Drainage connector 305mm
- HP101T4#00 Drainage connector 400mm

COLORS

- Silver (remote control, Body display part)

TECHNOLOGY & INNOVATION HIGHLIGHTS


- | | |
|--|---|
|  EWATER+ for WAND |  CEFIONTECT |
|  EWATER+ for BOWL |  TORNADO FLUSH |
|  EWATER+ for UNDER SEAT |  RIMLESS |
|  AIR-IN WONDER-WAVE |  WATER SAVING |
|  WARM AIR DRYING |  AUTO OPEN/CLOSE LID |
|  HEATED SEAT |  AUTO FLUSH |
|  DEODORIZER |  PREMIST |

CODES/STANDARDS

- Please refer to the label for product standards.

DIMENSIONAL DRAWINGS

CES8E120KCN · NEOREST One-piece Toilet



TOTO(CHINA) CO.,LTD. All rights reserved.

SPECIFICATIONS

CES8E120KCN	
额定电源	AC220V.50Hz
额定功率	834W
最大功率	1448W<进水温度0° C时>
温水加热方式	瞬间式
电源线长度	1.2m
防水保护等级	IPX4
水效等级	2级
进水压力	最低必要水压: 0.05MPa<流动时>
	最高水压: 0.75MPa<静止时>
进水温度	0-35° C
使用温度	0-40° C
产品尺寸	宽411mm×长725mm×高497mm
产品重量	约50kg

便器部		
坐便器	冲洗水量	大3.8L, 小3.0L
	名义冲水量	3.3L
	进水方式	管道直压与内置水箱储水混合式
	冲洗方式	喷射虹吸式
	尺寸	加长型

机能部		
洗净装置	喷水量	臀部洗净: 0.32-0.43L/min
		臀部轻柔洗净: 0.32-0.43L/min
		下身洗净: 0.29-0.43L/min
		下身护理洗净: 0.35-0.43L/min
	水势调节	5档
	吐水温度	温度调节范围: 关, 约30-40° C
加热便座	加热器功率	1200W
	安全装置	温度保险丝
	防逆流装置	真空开关, 止回阀
除臭装置	方式	○2除臭
	风量	标准模式: 约0.09m³/min 强力模式: 约0.16m³/min
温风干燥	功率(耗电量)	标准模式: 约1.6W 强力模式: 约4.0W
	温风温度	温度调节范围: 约35-60° C
	风量	约0.25m³/min
	加热器功率	261W
	安全装置	温度保险丝

TOTO(CHINA) CO.,LTD. All rights reserved.